

OpenScape Desk Phone CP telephone family

The OpenScape Desk Phone CP family offers three meticulously conceived, compact and easyto-administer devices to fulfill the infinitely varied needs of a multitude of users.



Intuitive, space-saving and convenient

The ergonomically designed, userfriendly and economical devices of the OpenScape Desk Phone CP telephone family are equipped with a wide variety of functions. They can be easily and conveniently operated, without having to make any compromises in the crystal-clear HD audio quality or performance.

Interoperability

The OpenScape Desk Phone CP family provides for interoperability between the office telephone and other devices via Bluetooth®, incl. Bluetooth LE Beacon facilitated by Eddystone™.NFC (Near Field Communication) and Circuit make these telephones into a highperformance communications center.

Devices of the OpenScape Desk Phone CP family can be integrated in existing IT/IP infrastructures without any problems. Each telephone features an integrated Ethernet switch and is supplied with electrical power by means of Power over Ethernet.



Main menu for the CP600

| 1 Conversations | 9 |
|--|-------|
| Sandra Rothenbaum | Now 🥑 |
| Maria Winter → Start new conversation | |
| Alyssa Bern Start new conversation |) |
| Anthony Fitzgerald Start new conversation |) |

Establish a call



Incoming call

New and state-of-the art user interface

The colored graphical user interface of the Desk Phone CP600 provides clear legibility and is therefore also easily and intuitively operable during a phone call. All necessary information and functions can be readily recognized.

Circuit integration

Unify is the first company to offer the integration of OpenScape Desk Phone CP400/CP600 devices with the Circuit Collaboration software. This integration provides Unify customers with more comprehensive possibilities for working together within a team. Learn more at www.yourcircuit.com.

Acoustics

OpenScape Desk Phone CP works with the latest advances in the field of acoustics, and thus offers superb voice quality in the hand-held unit and hands-free mode.

All models are standard-equipped with a high-quality hands-free feature. In addition, each model offers a connection option for professional headsets.



The OpenScape Desk Phone CP product family offers the industry's leading HD voice transmission – AudioPresence[™] HD.

AudioPresence[™] HD ensures that the users of these telephones can get an immersive audio experience for voice calls and audio conferences. AudioPresence[™] HD is provided for the entire portfolio of the Open-Scape Desk Phone CP product family.

AudioPresence[™] HD leverages the standards-based G.722 high-definition audio codec, best-in-class speaker, microphone and acoustic components, as well as advanced noise suppression and echo cancellation on all Desk Phone CP models.

Operational software

- SIP software is pre-installed
- Plug & Play / automatic software deployment via DLS
- CorNet-IP / HFA (CP200)

Phone models

OpenScape Desk Phone CP200

Outstanding voice quality, an extensive scope of features and a two-line display make this device the ideal choice for users with UC/CTI support.



Display

- Graphical two-line display (192 x 48 pixels), monochrome
- Signaling LED (red/green/orange)

Keys

- 4 freely-programmable function keys with an LED (red/green/orange) Pre-assignment: call log, contacts, forwarding, redialing
- 5 fixed function keys, 3 with LED (red or green): hold, transfer, conference calling, settings, messages
- 4-way navigator plus OK key
- 3 audio function keys (mute/loudspeaker/headset) with LED
- Volume +/-
- Open listening/hands-free speaking (full duplex)

Connection options

Headset interface (DHSG/EHS)

Placement

- Base, two different placement angles
- Wall-mounting

OpenScape Desk Phone CP400

The larger display and individual options for customization make this telephone the ideal solution for office workplaces and teams.



Display

- Pivotable graphical display, 3.7" (240 x 120 pixels), monochrome
- LED backlighting (white)
- Signaling LED (red/green/orange)

Keys

- 4 context-sensitive softkeys with LED (red/green/orange)
- 2 fixed function keys (menu/absence)
- 16 freely-programmable function keys with LED (red/green/orange)
- 4-way navigator plus OK key
- 3 audio function keys (mute/loudspeaker/headset) with LED
- Volume +/-
- Open listening/hands-free speaking (full duplex)

Connection options

• Headset interface (DHSG/EHS)

Placement

Base, two different placement angles

OpenScape Desk Phone CP600

This device was developed for demanding users and provides crystalclear HD voice quality, a brilliant color display and a broad range of functions.



Display

- Pivotable graphic color display, 4.3" (480 x 272 pixels)
- LED backlighting (white)
- Signaling LED (red/green/orange)

Keys

- 5 context-sensitive softkeys with LED (red/green/orange)
- 2 fixed function keys (menu/absence)
- 4-way navigator plus OK key
- 3 audio function keys (mute/loudspeaker/headset) with LED
- Volume +/-
- Open listening/hands-free speaking (full duplex)

Connection options

- Headset interface (DHSG/EHS)
- Bluetooth 2.1 BR/EDR
- Bluetooth 4.1 LE
- NFC
- Slot for SD card

Placement

- Base, two different placement angles
- Wall-mounting

Accessories

Key module KM400

The key module KM400 can also be connected to the Desk Phone CP400.

The 16 freely-programmable keys with LED signaling can have various functions assigned as desired.



- 16 freely-programmable keys with LEDs (red/green/orange)
- Key labeling using paper inlays
- Max. 2 key modules connectible to a CP400
- Only usable on CP400

Key module KM600

The key module KM600 can also be connected to the Desk Phone CP600.

Each of the 12 freely-programmable keys with LED signaling can be assigned with functions on two levels. This supplementally increases the possible scope of functions.

The high-contrast, monochrome TFT display enables comfortable and perfectly legible labeling of each key.



- 12 freely-programmable keys with LEDs (red/green/orange)
- Key labeling by means of a monochrome TFT display
- 2 navigation keys for switching between the first and second levels
- Max. 4 key modules connectible to a CP600
- Only usable on CP600

Communications platforms

The OpenScape Desk Phone CP product family supports SIP (Session Initiation Protocol) signaling. The CP200 also supports CorNet-IP / HFA.

The following communications platforms are supported:

SIP

- OpenScape Voice V7 R1
- OpenScape Voice V8
- OpenScape Voice V9
- OpenScape 4000 V8

HFA

- OpenScape Business V2 R2
- OpenScape 4000 V8

Technical data

| | Desk Phone CP200 | Desk Phone CP400 | Desk Phone CP600 | |
|--|---|-----------------------------------|---|--|
| Housing color | | black | | |
| Placement angle | | 2-stage | | |
| Handset and base embossed with Unify logo | Yes | | | |
| Display | | | | |
| Dimensions | Graphical two-line display | Graphical display, 3.7" | Graphical color display, 4.3" | |
| | 192 x 48 pixels | 240 x 120 pixels | 480 x 272 pixels | |
| Color | Monochrome | Monochrome | 16-bit color depth | |
| Backlighting | No | White LED | White LED | |
| Adjustable display | No | Yes | Yes | |
| Additional optical call alert | | Yes (red/green/orange) | | |
| Keys/LEDs | | | | |
| Context-sensitive softkeys | No | 4 with LED (red/green/ orange) | 5 with LED (red/green/ orange) | |
| Fixed function keys | 5 | 2 | 2 | |
| | 3 with LED | (Menu/absence) | (Menu/absence) | |
| | Hold, transfer, confer- ence calling, settings, messages | | | |
| Free-programmable keys | 4 with LED (red/green/orange) Pre-assignment: call log, contacts, forwarding, re- dialing | 16 with LED (red/green/orange) | None Alternative: 4 favorites with LED (red/green/ orange) | |
| Key labeling | Paper | Paper | Display | |
| Audio keys | Tuper | 3 | Diopiny | |
| | 3 (Mute/loudspeaker/headset) with LED Volume +/- | | | |
| Navigation | 4 | 4-way navigator, plus OK key | | |
| Audio | | | | |
| G.711 (64 kbit/s a/µ-law) | Yes | | | |
| G.722 (64 kbit/s) | Yes | | | |
| G.729AB (8 kbit/s) | Yes | | | |
| Open listening | Yes | | | |
| Full duplex handsfree | Yes | | | |
| Echo canceling for local echo (AEC) full duplex | Yes | | | |
| Interfaces | | | | |
| LAN connection (Ethernet with auto-sensing) | 10/100 Mbit/s | 10/100/1000 Mbit/s | 10/100/1000 Mbit/s | |
| Integrated switch | | Yes | I | |
| Energy Efficient Ethernet (IEEE 802.3az) | No | Yes | Yes | |
| Headset jack for cord-connected (121 TR9-5) and cordless headsets (121 TR9-5*) | | Yes | 1 | |
| Bluetooth V2.1 BR/EDR (hands-free profile, headset profile) | No | No | Yes | |

| | Desk Phone CP200 | Desk Phone CP400 | Desk Phone CP600 | |
|--|--------------------------------------|-----------------------|--|--|
| Bluetooth Low Energy 4.1 | No | No | Yes | |
| Passive RFID tag | Yes | | | |
| Passive NFC tag with:BT MAC addressLAN MAC address | No | No | Yes | |
| SD card slot | No | No | Yes | |
| VoIP protocol | | | | |
| SIP | Yes | | | |
| CorNet IP / HFA | Yes | No | No | |
| Expansions | | | | |
| Connection option for Key module | No | Yes Up to 2 KM400 | Yes Up to 4 KM600 | |
| Wall mounting kit | Yes | No | Yes | |
| Security features | | | | |
| Layer 2 authentication (IEEE 802.1x) | | Yes | | |
| Payload encryption via SRTP | Yes | | | |
| Signaling via TLS encryption | Yes | | | |
| Support of digital certificates (X.509 V3) | Yes | | | |
| HTTPS | Yes | | | |
| Network | | | | |
| LLDP-MED | | Yes | | |
| QoS (DiffServ and IEEE 802.1Q) | Yes | | | |
| IEEE 802.1Q | Yes | | | |
| Power supply | 1 | | | |
| Power over Ethernet (PoE, IEEE 802.af) | | Yes | | |
| PoE class | 1 | 2 | 2 | |
| OpenStage power supply (country-spe- cific models available) | Optional | Optional | Optional (always necessary as of the 2nd Key module) | |
| Certifications | | | | |
| Europe | CE mark | | | |
| USA/Canada | NRTL marking | NRTL marking | | |
| Safety standards | IEC60950-1, EN60950-1 | | | |
| | UL60950-1, CAN/CSA-C22 | .2 No.60950-1 | | |
| EMC standards | CISPR22 Class B, CISPR 24 | | | |
| | EN55022 Class B, EN55024 | | | |
| | FCC Part 15 (CFR 47) Class B | | | |
| Hearing aid compatibility (HAC) | FCC Part 68 (CFR 47) / CS-03 Part V | | | |
| Technical data | | | | |
| Dimensions (angle (°) x height [mm] x | 20° x 113 x 219 x 207 | 20° x 143 x 283 x 207 | 20° x 150 x 219 x 207 | |
| width [mm] x depth [mm]) | 45° x 173 x 219 x 165 | 45° x 189 x 283 x 165 | 45° x 193 x 219 x 165 | |
| Weight [kg] | 0.837 1.121 0.96 | | | |
| Storage conditions | -40 °C to +70 °C (-40 °F to +158 °F) | | | |
| Operating conditions | +5 °C to +40 °C (+41 °F to +104 °F) | | | |

Notes



Copyright © Unify Software and Solutions GmbH & Co. KG, 03/2017 Mies-van-der-Rohe-Str. 6, 80807 Munich/Germany

All rights reserved.

Reference No.: A31002-C1000-D101-4-7629

The information provided in this document contains merely general descriptions or characteristics of performance which in case of actual use do not always apply as described or which may change as a result of further development of the products. An obligation to provide the respective characteristics shall only exist if expressly agreed in the terms of contract.

Availability and technical specifications are subject to change without notice.

Unify, OpenScape, OpenStage and HiPath are registered trademarks of Unify Software and Solutions GmbH & Co. KG. All other company, brand, product and service names are trademarks or registered trademarks of their respective holders.



unify.com